

# IFC200

## USB DATA LOGGER INTERFACE



### Features

- Compatible With Most MadgeTech Data Loggers
- "Plug and Play" - No Driver Installation Required
- Blue, Green and Red LED Indicators
- Reduced noise with longer sensor leads

MadgeTech's IFC200 interface cable communicates between stand alone data loggers and the MadgeTech software. Through this interface, loggers can be started, stopped or downloaded.



The IFC200 has been redesigned, and is now "plug and play". It can be directly connected to a computer without installing any drivers. The improved IFC200 can now operate at up to 500 Volts RMS relative to the computer's earth ground when attached.

The IFC200 is equipped with communication LE device status. The blue light illuminates when the device is plugged in and successfully recognized by Windows. The red light flashes when data is sent, and the green light flashes when data is received.



## IFC200 SPECIFICATIONS\*

**Operating Environment:** -20°C to +50°C  
(-4°F to +122°F)

**Materials:** Polycarbonate Enclosure

**Dimensions:** Enclosure: 1.9" x 0.69" x 0.32  
(48.4mm x 17.5mm x 8.1mm)

**Dimensions:** Cable: 6' included  
May be used with any shielded 3.5mm stereo cable up to 100'

**LEDS:** Blue and Red/Green

Blue: Illuminates when the device is plugged in and successfully recognised by Windows.

**LED Functions:** Red: Flashes when data is sent.

Green: Flashes when data is received.

\*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SPECIFIC WARRANTY REMEDY LIMITATIONS APPLY. CALL 1-603-456-2011 OR GO TO WWW.MADGETECH.COM FOR DETAILS.

## ORDERING INFORMATION

MODEL	DESCRIPTION
IFC200	USB Data Logger Interface

販売代理店:



株式会社 クローネ

本社: 〒124-0023 東京都葛飾区東新小岩3丁目9番6号 TEL: (03)3695-5431 FAX: (03)3695-5698  
大阪支店: 〒530-0054 大阪市北区南森町2-2-9 (南森町八千代ビル7F) TEL: (06)6361-4831 FAX: (06)6361-9360  
e-mail: sales-tokyo@krone.co.jp URL: http://www.krone.co.jp