



New table pump in the portfolio

-0.95...160 bar

As separate pump or incl. accessories in case

Typically available from stock

End of
Q1/2023
available

The new P160.T

Pneumatic table-top test pump
with expanded pressure range

Pneumatic table-top test pump // -0.95...160 bar

P160.T



P160.T Basic



P160.T Solid



Highlights

- No contamination of the test sample with oil or water
- Pneumatic up to 160 bar
- Minimal force required to reach 160 bar
- Quick exchange of test samples due to quick couplings
- Fine adjustment valve for exact setting of the test pressure

Technical data

Type	P160.T
Pressure ranges	
Vacuum	-0.95 bar
Overpressure	160 bar
Pressure medium	Air
Connections	
Reference pressure gauge	G $\frac{1}{4}$ with quick coupling
Test sample	G $\frac{1}{4}$ with quick coupling
Basic	
Dimensions	Approx. 470 x 262 x 170 mm
Weight	Approx. 6 kg
Solid	
Dimensions (case)	Approx. 575 x 470 x 230 mm
Weight	Approx. 10.2 kg
+ Adapter kit	Brass chrome plated
+ Seal kit	PA flat gaskets and O-rings

Article numbers

Order code			
Type	Version		Order number
P160.T	Lever pump	Basic Solid (incl. case and adapter)	EPPT160EBL0000 EPPT1600BL0000



株式会社 **クローネ**

■カタログに掲載してある製品の色は印刷インキの関係上、実際とは異なる場合があります。
■製品のデザイン、仕様等などは、予告なく変更する場合があります。

本 社：〒124-0023 東京都葛飾区東新小岩3丁目9番6号 TEL: (03) 3695-5431 / FAX: (03) 3695-5698
大阪支店：〒530-0054 大阪市北区南森町2-2-9(南森町八千代ビル7F) TEL: (06) 6361-4831 / FAX: (06) 6361-9360
e-mail: sales-tokyo@krone.co.jp URL: <https://www.krone.co.jp>